



RG ALUMINIUM OXIDE flap wheels on threaded shaft

Description:

Aluminium oxide flaps and X-Flex weight backing 1/4-20 UNC shaft thread.

Main features and benefits:

Being quick to change, our RG flap wheels on threaded shaft can be ideally used in robotized applications or intensive production lines. In addition to this, it is extremely easy to switch over to a new grit on the same tool by manually unscrewing the wheel.

Recommended applications:

Finishing small parts, moulds, alloy wheels, robotized applications.

Work surfaces:

Stainless steel, standard steel, alloyed steel, aluminium, titanium, nonferrous materials and alloys, plastic materials, glass fibre, rubber, marble.

diam/th/shaft	max	rpm		P60	P80	P120	P180	P240	P320
25x15xTH	38.200	27.500	10	RG0463	RG0464	RG0465	RG0466	RG0467	RG0468
25x25xTH	38.200	27.500	10	RG0475	RG0476	RG0477	RG0478	RG0479	RG0480
30x10xTH	31.800	22.900	10	RG0481	RG0482	RG0483	RG0484	RG0485	RG0486
40x25xTH	23.800	17.100	10	RG0487	RG0488	RG0489	RG0490	RG0491	RG0492
50x25xTH	19.000	13.700	10	RG0499	RG0500	RG0501	RG0502	RG0503	RG0504



extended shaft for RG with threaded shaft

length/diameter	
50x6	00Y23
80x6	00Y20